



## ND Series

Electrified cylindrical lock



### Overview

Many of the most advanced electronic access systems still rely on the strength and functionality of the mechanical lock hardware on the door. ND Series electrified locks feature Schlage's most robust cylindrical design built for performance, security and durability. It is a "beyond grade 1" lock in terms of strength and can be used as part of an integrated system or as a standalone solution with a buzzer or other device as the controller.

The Schlage ND cylindrical lock uses a motor instead of a solenoid to provide quiet operation and energy efficiency. The maximum current draw of 0.23 amps allows more locks to run off a single power supply. A low, 0.010 amp holding current eliminates any potential for hot levers in electrically locking applications or in electrically unlocking applications where the door is left open for long periods of time. ND Series can be quickly and easily installed and is compatible with various key systems for field adaptability. It suites seamlessly with the other ND Series hardware which includes both purely mechanical and fully electronic solutions.

When it comes to access control, mechanical components are just as important as their electronic counterparts. The Schlage ND Series provides versatility and easy installation to complete your access control system.

### Recommended applications

The wired electrified ND Series is ideal for new construction and high traffic areas where hardwired power ensures continuous operation and where electrified door prep, hinges and wiring can easily be incorporated into the building. The electrified ND Series is regularly used as part of an access control system for high security areas, or independently in areas that require a remote access switch.

### Features and benefits

- Exceeds ANSI A156.2 series 4000 Grade 1 torque requirements
- Universal input voltage – accepts 12V or 24V DC for installation flexibility
- Change operation mode between Electrically Unlocking (EU or Fail Secure) or Electrically Locking (EL or Fail Safe) by simply flipping a switch on the chassis
- Low maximum current draw allows multiple locks on a single power supply
- Low holding current produces minimal heat, eliminating "hot levers" in electrically locking applications
- Request-to-exit functionality can be easily upgraded in the field with the following kit part #: N123-062
- Extensive options for lever styles, finishes and functions
- UL listed for 3-hour fire door
- Available with Vandlgard® lever engagement on storeroom function - ideal for areas subject to abuse or vandalism

## ND Series mechanical specifications

|                         |   |
|-------------------------|---|
| Handing                 | Non-handed  |
| Door thickness          | 1 5/8" to 2 1/8" standard including Vandlgard   |
| Backset                 | 2 3/4" standard, 2 3/8", 3 3/4" and 5" optional   |
| Faceplate               | Brass or stainless steel; 1 1/8" x 2 1/4" (29 mm x 57 mm) square corner, beveled  |
| Lock chassis            | Zinc plated for corrosion resistance  |
| Latchbolt               | Steel, 1/2" (12 mm) throw, deadlocking on keyed and exterior functions; 3/4" (19 mm) throw anti-friction latch available for pairs of fire doors                                |
| Exposed trim levers     | Pressure cast zinc, plated to match finish symbols  |
| Roses                   | Brass   |
| Strike                  | ANSI curved lip strike 1 1/4" x 4 7/8" x 1 3/16" lip to center standard   |
| Cylinders and keys      | Standard: 6-pin, solid brass cylinder is standard in the patented Schlage Everest 29 S123 keyway; two nickel silver cut keys per lock; additional keying options available      |
| Keying options          | Available in full size interchangeable core (FSIC) and small format interchangeable core (SFIC). Also available less cylinder and less FSIC to allow for Primus cylinder usage. |
| Lever design and finish | All ND levers and all ND finishes available   |

## ND Series electronic specifications

|  |  |
|--|--|
| Voltage  | Auto-detects 12 through 24V DC operation     |
| Peak current   | .23 amps (230mA)                             |
| Holding current  | 0.01 amps (10mA)                             |
| Operating temperature  | Maximum +120°F (+49°C)<br>Minimum 32°F (0°C) |
| Micro switch electrical rating for request-to-exit (N523-194) function | 2 amps 30V DC                                |


## ND Series electrified functions

|                  |  |
|------------------|--|
| No cylinder      | ND12DEL: Electrically Locking/Fail Safe<br>ND12DEU: Electrically Unlocking/Fail Secure   |
| Outside cylinder | ND80PDEL: Electrically Locking/Fail Safe<br>ND80PDEU: Electrically Unlocking/Fail Secure |
| Vandlgard        | ND96PDEL: Electrically Locking/Fail Safe<br>ND96PDEU: Electrically Unlocking/Fail Secure |

Note: See pricebook for additional details.

## Vandlgard®

Vandlgard trim is specifically designed for highly abusive environments. The outside lever rotates freely up and down when locked, limiting the ability of vandals to apply excessive force to the chassis.



## About Allegion

Allegion (NYSE: ALLE) is a global pioneer in seamless access, with leading brands like CISA®, Interflex®, LCN®, Schlage®, SimonsVoss® and Von Duprin®. Focusing on security around the door and adjacent areas, Allegion secures people and assets with a range of solutions for homes, businesses, schools and institutions. Allegion had \$2.7 billion in revenue in 2020, and its security products are sold around the world. For more, visit [www.allegion.com](http://www.allegion.com)

KRYPTONITE ■ LCN ■  ■ STEELCRAFT ■ VON DUPRIN

Allegion, the Allegion logo, Schlage, and the Schlage logo are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.



© 2022 Allegion  
004999, Rev. 02/22  
[www.allegion.com/us](http://www.allegion.com/us)